



HUXXA FT 100

POLYMER BASED TILE ADHESIVE



USE

- Ceramic tiles
- Porcelain tiles
- Medium Porosive stone

SUBSTRATE

- Plaster
- Cement base surface
- RCC Surface
- AAC block surface
- Mosaic tile surface

COVERAGE

2.50 to 3 Sqft. per Kg in 3mm bed thickness
Using 6mmx6mm notch trowel

COLOURS AVAILABLE

Grey

Packing

20 & 40 Kg

GRADE : IS -T1

HUXXA NSA 200

POLYMER BASED TILE ADHESIVE



APPLICATION AREAS

- Ceramic Tiles
- Porcelain Tiles
- Vitrified Tiles
- Small Size Stones

SUITABLE SUBSTRATES

- Plaster
- Cement-Based Surfaces
- RCC Surfaces
- AAC Block Surfaces
- Mosaic Tile Surfaces
- Stone & Red Brick Surfaces

COVERAGE

2.50 to 3 Sqft. per Kg in 3mm bed thickness
Using 6mmx6mm notch trowel

COLOURS AVAILABLE

White & Grey

Packing

20 & 40 Kg

GRADE : IS/BS -C2T

HUXXA VT 300

POLYMER BASED TILE ADHESIVE



USE

- Big Formats
- Natural Stone

SUBSTRATE

- Plaster
- Cement base surface
- RCC Surface
- AAC block surface
- Tile On Tile
- Stone & red brick surface

COVERAGE

2.50 to 3 Sqft. per Kg in 3mm bed thickness
Using 6mmx6mm notch trowel

COLOUR

WHITE & GREY

Packing

20 & 40 Kg

GRADE : IS/BS -C2TE

HUXXA GTA 400

POLYMER BASED TILE ADHESIVE



APPLICATION AREAS

- Ceramic Tiles
- Vitrified Tiles
- Glass Mosaic tiles
- Big formats Tiles Stones

SUITABLE SUBSTRATES

- Plaster
- Cement-Based Surfaces
- AAC Block Surfaces
- Mosaic Tile Surfaces
- Stone & Red Brick Surfaces
- Red brick surface

COVERAGE

2.50 to 3 Sqft. per Kg in 3mm bed thickness
Using 6mmx6mm notch trowel

COLOURS AVAILABLE

White & Grey

Packing

20 Kg

GRADE : IS/BS -C2TES1

HUXXA FPA 500

TWO COMPONENT FLEXIBLE ADHESIVE



APPLICATION INSTRUCTIONS

All types tiles, glass mosaic tiles, large format tiles, precast terrazzo, all-natural stones, large thin/ slim tiles, composites / artificial / nano engineered stone, metal & glass tiles.

Features

- Water-proof
- Long open time
- High tensile, Compression and shear strength
- Safe application and Multi-purpose use
- Hardening without shrinkage
- Excellent durability and Resistant to ageing

PACKING

4 Kg PACK

PART A: 3.650Kg

PART B: 0.350Kg

COVERAGE

- 16-20 sq.ft. / 4 Kg pack 1.5mm bed thickness (using 3mm x 3mm notch)
- 8-10 sq.ft. / 4 Kg pack 3mm bed thickness (using 6mm x 6mm notch)



METAL PLATE



WOOD



ONE ADHESIVE
MULTI SURFACE USE



ONE ADHESIVE – ONE SOLUTION
FOR METAL, WOOD & MORE

HUXXA BJM 33

BLOCK JOINTING MORTAR



USE

- Light weight block jointing mortar work
- Brick application mortar work

ADVANTAGES

- High bonding strength
- High surface area coverage
- Helps to reduce shrinkage cracks or shortness
- Economical and easy to use

SUBSTRATES:

- AAC Blocks
- Concrete hollow blocks
- Light weight masonry blocks
- Cellular concrete blocks
- Fly Ash Bricks
- Clay Bricks

PACKING

40Kg

COVERAGE

155 to 165 sq.ft / 40 kg / 3mm bed thickness



HUXXA RMP 34

EASY TO USE PREMIX PLASTER



APPLICATION

Apply mixed plaster evenly with steel trowel. Level to required finish using masonry tools (steel trowel/wooden float/sponge).

MIXING

Mix 40 kg bag with 6.5–6.8 L clean water. Use mechanical mixer for uniform mix. Rest 5 min before use.

PACKING

40 kg bag

COVERAGE

15–18 sq.ft / 40 kg (10–12 mm thickness on RCC/AAC block).

HUXXA FL 35

FLOOR HARDENER



APPLICATION

A high-quality cementitious dry shake floor hardener with superior abrasion resistance. The material is non-metallic and non-oxidising, and is free from organic impurities. Manufactured using a graded composition of cement, additives, aggregates and polymer modifiers, ensuring ease of placing, excellent compaction and smooth finishing

RECOMMENDED AREAS

- Industrial floors
- Warehouses & workshops
- Parking & loading areas
- Garages & car wash floors
- Aircraft hangars & helipads
- Automobile assembly houses

PACKING

40 kg

HUXXA MRM 36



FEATURES & BENEFITS

- For repairs to damaged reinforced concrete elements particularly where access is restricted and where vibration of the placed material is difficult or impossible

- Suitable for various structural strengthening measures such as filling honeycombs and cracks

PACKING

40 Kg Bag

HUXXA FG 37



USE

- Free Flow
- High Strength
- Self Curing
- Smooth Flow & Level Finish
- Diaphragm wall bolt anchoring

COVERAGE

- Heavy machinery foundation grouting
- Steel structure Foundation anchoring
- Core-cut gap filling & repair works

PACKING

40 Kg Bag

HUXXA WCC 38



APPLICATION

White cement gives superior fineness and whiteness. It has a high refractive index and high strength it gives smooth finish even when blended with pigments. It gives you the freedom to play with a wide palette of colours, textures, shapes & sizes, and is the most preferred when it comes to decorative paints, plasters, mosaic tiles, terrazzo flooring and white cement-based-value-added products.

PACKING

1, 5 & 20Kg Bags

HUXXA WALL PUTTY 39



FEATURE

- Wall plaster
- Ceilings
- RCC surfaces
- Repair works
- Smoothing of walls for both indoor and outdoor
- Renders a smooth and durable surface
- Under layer for all kinds of decorative paints

ADVANTAGES

- Suitable for both internal and external applications
- Water-resistant
- Excellent adhesion to host substrate
- Smooth finish
- Low water absorption
- Suitable for leveling prior to the application of oil based or water based coatings

PACKING

20 & 40 Kg Bags

COVERAGE

30-32 sq.ft. / Kg. / 1 mm Thickness

HUXXA EG 2K



USE

- Wall & Floor Tiles & Stone
- Laboratories
- Food processing plants
- Hospitals, abattoirs
- Kitchen and swimming pools etc.

ADVANTAGES

- Easy Application
- Better Durability
- Waterproof
- Can be used for both interior and exterior uses
- Excellent resistance to acid and alkalis

PACKING

1 & 5 Kg PACK
PART A: 700gm
PART B: 300gm

COVERAGE

170 R. ft per / kg. / 3mm x 3 mm groove size

HUXXA EG 2 PART EPOXY GROUT



APPLICATION

Spread the HUXXA EG Epoxy mix generously with float making sure to fill all gaps completely. Add fresh mix frequently to ensure that all parts of the surface are properly grouted. Start from one end and work towards the opposite end in smooth continuous motions coating the surface as evenly as possible. Work from the bottom to up when grouting walls. Use the edge of the float to remove excess grout. Exposed to an ambient temperature of 30°C the grout must be applied within 35 minutes of mixing.

PACKING

1 & 5kg
PACK PART A: 900gm PART B: 100gm

COVERAGE

170 Rft. per / kg. / 3mm x 3 mm groove size

METALLIC GROUT & NIGHT VISION GROUT AVAILABLE

HUXXA EG 3K

HIGH PERFORMANCE EPOXY GROUT



USE

- Wall & Floor Tile & Stone
- Laboratories
- Food processing plants
- Hospitals, Kitchen and swimming pools etc.

ADVANTAGES

- Easy for fast application
- Better durability
- Waterproof
- Can be used for interior
- Excellent resistance to acid and alkalis
- High bond strength to steel, concrete and tiles

PACKING

1 & 5 Kg PACK
PART A: 200gm
PART B: 100gm
PART C: 700gm

COVERAGE

150 Rft. per / kg 3mm x 3 mm

HUXXA CPG

POLYMER MODIFIED GROUT



USE

- Vitrified tile
- Marble
- Natural stone
- To fill the tile joints with grout so as to create strong long lasting tile joints

ADVANTAGES

- Extra fine finish
- High resistance to sunlight
- Easy to clean
- High performance grout
- Excellent water resistance
- Designed for grouting wall & floor tiles, marbles, & stones etc.
- Natural antibacterial

PACKING

500gm & 1kg PACK

COVERAGE

90 Rft. per / kg. / 3mm x 3 mm

HUXXA VALENS

SUPER STRENGTH, MULTIPURPOSE EPOXY ADHESIVE



FEATURES

High strength system
Medium curing system

BENEFITS

Can bond almost any substrates
Cost-effective system

APPLICATION AREAS

Kitchen & window framing
Marble & granite fixing
Wood to wood
Wood to marble
Steel railing grouting

MIXING RATIO

100 : 80 by weight
100 : 100 by volume

COVERAGE

75–80 sq. ft. per 1.8 Kg set

PACKING

450gm, 900gm, 1.8Kg, 9Kg & 90 Kg



HUXXA MULTI POTENS

SUPER STRENGTH EPOXY ADHESIVE MEDIUM CURING SYSTEM



FEATURES

Super strength epoxy adhesive
Medium curing system

BENEFITS

Can bond almost any substrates
No shrinkage

APPLICATION AREAS

Ceramics
Automobiles
Wood Industry
Sports goods
Civil industry
Metal to rubber

MIXING RATIO

100 : 80 by weight
100 : 100 by volume

COVERAGE

75–80 sq. ft. per 1.8 Kg set

PACKING

1.8Kg, 9Kg & 90 Kg



HUXXA SBR 10



USE

- Waterproofing sunk, bathrooms, chajjas & lift pits, & balconies.
- Liquid & effluent tanks, car deck and walk ways.
- Repairs of plaster cracks more than 5 mm & in gaps developed between masonry and RCC members.
- As bonding slurry coat for pin hole treatment on concrete surface & as repair mortar for overhead applications.
- As a bond coat plaster to plaster, concrete-to-old concrete, plaster to concrete masonry to stone work etc.

PACKING

500gm, 1, 5, 20, 50 and 200 kg

HUXXA SBR 11



USE

- Waterproofing sunk, bathrooms, chajjas & lift pits, & balconies.
- Liquid & effluent tanks, car deck and walk ways.
- Repairs of plaster cracks more than 5 mm & in gaps developed between masonry and RCC members.
- As bonding slurry coat for pin hole treatment on concrete surface & as repair mortar for overhead applications.
- As a bond coat plaster to plaster, concrete-to-old concrete, plaster to concrete masonry to stone work etc.

PACKING

500gm, 1, 5, 20, 50 and 200 kg

HUXXA ABP 12

SINGLE COMPONENT POLYMER FOR CEMENT BASED
WATERPROOFING COATING



USE

- Roofs, terraces and balconies
- Pools and fountains• Water Storage Tank
- RCC & Masonry
- Reservoirs and channels
- End walls subjected to rain

PACKING

1, 5, 10 & 20 Kg

HUXXA SHIELD 2K 13



USE

- Water tanks, Swimming pools
- Roofs and terrace of all types of low & high rise building
- To re-face and even out variations in concrete and masonry surfaces
- To seal concrete masonry walls and bridges the shrinkage cracks which are static
- To provide a tough and durable coating which cannot be easily damaged or worn away

PACKING

3Kg, 15Kg & 30Kg set

COVERAGE

5-7 sq.ft. / Kg. / Two Coat

HUXXA LW 22

INTEGRAL WATERPROOFING COMPOUND



USE

Use cement mortar, cement plaster & cement concrete

BENEFITS

- Increases strength,
- Improves work ability
- Reduction in corrosion of steel
- Makes cohesive concrete

APPLICATION PROCEDURE

Add 200gm in a 50kg cement bag

PACKING

1, 5, 10, 20, 50 and 200 kg

DOSEGE

200 ml / 50Kg. Bag of cement

HUXXA SILCOAT 15 & 16

HEAVY DUTY REINFORCED ACRYLIC WATER PROOF COATING FOR TERRACE / EXTERIOR WALL



USE

- Building roofs / Terraces- Flat & slope
- RCC Structure
- Over existing cementitious waterproofing treatments like brick-bat coba & Concrete Screeds

ADVANTAGES

- Film thickness – Provides higher dry film thickness of minimum 1 mm in three coat application Crack bridging – Good Bridges cracks
- Suitability - Can be used for flat as well as sloping roofs
- Easy for Applicable – By Brush & Roller

PACKING

1, 4 & 20Kg

COLOUR

WHITE & BLACK

COVERAGE

10-12 sq.ft. / Kg. / Two Coats for

HUXXA WM 17



USE

- Building roofs / Terraces-Flat & slope
- RCC Structure
- Masonry Walls

ADVANTAGES

- High Film thickness
- Crack bridging Property
- U.V. Resistance
- Long Lasting
- Breath ability

PACKING

4 & 20Kg

COVERAGE

10-12 sq.ft. / Kg. / Two Coats

HUXXA BM 18



USE

- Bathroom, Sunks, Water tank, Retaining Walls, Life pits

ADVANTAGES

- Single component
- Easy to apply, Cost effective
- Quick drying
- Excellent Adhesion strength

PACKING

20Kg Pack

COVERAGE

10-12 sq.ft. / Kg. / Two Coats

HUXXA 1K PU 19



APPLICATIONS

After 24 hours of duration time at room conditions, it should be mixed with a low circuit mixer and suitable tool to mix, until the mixture be homogenous. HUXXA 1K PU 19 can be applied using a brush or roller. A minimum thickness of 1mm dried film thickness of HUXXA 1K PU 19. Layer should protect from water, rain, external effects, and mechanic compulsion.

- FAST CURING
- EXCELLENT ADHESION
- LOW ODOUR
- RESISTANCE TO PEDSTRION & LIGHT
- VEHICLE TRAFFIC
- SINGLE COMPONENT, EASY TO APPLY
- RESISTANCE TO WATER AND UV.

PACKING

25Kg Packs

COVERAGE

8 - 10 Sq ft. / Kg / Two coats

HUXXA CRACK & FIX



APPLICATION

- Concrete Primer
- Epoxy Injection Grout
- Epoxy Mortar
- Repair Compound
- Bonding Agent for Old & New Concrete

COVERAGE

- Primer application
40 sq ft for 150 micron thickness per kg
- Screed application
4.5-5 sq for 1mm thickness per Kg

PACKING

1.5, 7.5 & 45Kg



SHREEJI CONCHEM

Office No- B-616, KP Epitome Near, lake, Makarba, Ahmedabad, Gujarat - 380051

☎ 7016970041 🌐 www.huxxa.in ✉ shreejiconchem@gmail.com